



SAFETY DATA SHEET ARDEX DPM 1 C Part A

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ARDEX DPM 1 C Part A

SUPPLIER Ardex UK Limited
Homefield Road
Haverhill
Suffolk
CB9 8QP
Tel. 01440 714939
Fax. 01440 716667
e-mail:
safetydatasheets@ardex.co.uk

EMERGENCY TELEPHONE +44 (0) 870 190 6777 (24 hours)

2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Air release agent		64742-47-8	1-5%	Xn;R65.
epoxy resin		55492-52-9	10-30%	Xi;R36/38. N;R51/53. R43.
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	10-30%	R43 Xi;R36/38 N;R51/53
LEVELLING ADDITIVE			1-5%	Xn;R65. Xi;R36/37. N;R51/53. R10.
N-METHYL-2-PYRROLIDONE	212-828-1	872-50-4	< 1%	Xi;R36/38
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS		68609-97-2	5-10%	R43 Xi;R38
Polyether modified trisiloxane		134180-76-0	1-5%	Xn;R20. Xi;R36. R52/53.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

ARDEX DPM 1 C Part A

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
N-METHYL-2-PYRROLIDONE	WEL	25 ppm(Sk)	103 mg/m3(Sk)	75 ppm(Sk)	309 mg/m3(Sk)

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Green Red
ODOUR	Characteristic
SOLUBILITY	Immiscible with water

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

ARDEX DPM 1 C Part A**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTSFire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).**11 TOXICOLOGICAL INFORMATION****INHALATION**

Irritating to respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

UK ROAD CLASS	9		
PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), epoxy resin)		
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	9	ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III	HAZARD No. (ADR)	90
ADR LABEL NO.	9	HAZCHEM CODE	3Z
CEFIC TEC(R) NO.	90GM6-III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
EMS	F-A, S-F	MARINE POLLUTANT	No.
UN NO. AIR	3082	AIR CLASS	9
AIR PACK GR.	III		

15 REGULATORY INFORMATION**LABELLING**

ARDEX DPM 1 C Part A



Irritant



Dangerous for the environment

CONTAINS

epoxy resin
 EPOXY RESIN (Number average MW <= 700)
 OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

RISK PHRASES

R43 May cause sensitisation by skin contact.
 R36/38 Irritating to eyes and skin.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S37 Wear suitable gloves.
 S24/25 Avoid contact with skin and eyes.
 S60 This material and its container must be disposed of as hazardous waste.
 S61 Avoid release to the environment. Refer to special instructions/safety data sheets.
 P5 Contains epoxy constituents. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION DATE 20/05/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R10 Flammable.
 R20 Harmful by inhalation.
 R36 Irritating to eyes.
 R36/37 Irritating to eyes and respiratory system.
 R36/38 Irritating to eyes and skin.
 R38 Irritating to skin.
 R43 May cause sensitisation by skin contact.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R65 Harmful: may cause lung damage if swallowed.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.