



## SAFETY DATA SHEET

### Ardex DPM Part B

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME                   Ardex DPM Part B

SUPPLIER                         Ardex UK Limited  
Homefield Road  
Haverhill  
Suffolk  
CB9 8QP  
Tel. 01440 714939  
Fax. 01440 716667  
e-mail:  
safetydatasheets@ardex.co.uk

EMERGENCY TELEPHONE       +44 (0) 870 190 6777 (24 hours)

#### 2 HAZARDS IDENTIFICATION

Causes burns. May cause sensitisation by skin contact. Harmful by inhalation and if swallowed. Possible risk of impaired fertility.

CLASSIFICATION                Xn;R20/22. Rep 3;R62. C;R34. R43.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	202-013-9	90-72-2	10-30%	Xn;R22 Xi;R36/38
3-AMINOPROPYLDIMETHYLAMINE	203-680-9	109-55-7	10-30%	R10 C;R34 Xn;R22 R43
4,4'-ISOPROPYLIDENEDIPHENOL	201-245-8	80-05-7	10-30%	Repr. Cat. 3;R62 R43 Xi;R37,R41
BENZYL ALCOHOL	202-859-9	100-51-6	30-60%	Xn;R20/22
ISOPHORONEDIAMINE	220-666-8	2855-13-2	10-30%	C;R34 Xn;R21/22 R43 R52/53
m-PHENYLENEBIS(METHYLAMINE)	216-032-5	1477-55-0	10-30%	Xn;R20/22. C;R34. R43,R52/53.

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Keep the affected person warm and at rest. Get prompt medical attention.

##### INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

##### SKIN CONTACT

Remove affected person from source of contamination. Rinse the skin immediately with lots of water. Get medical attention promptly if symptoms occur after washing.

##### EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

##### UNUSUAL FIRE & EXPLOSION HAZARDS

No unusual fire or explosion hazards noted.

##### SPECIFIC HAZARDS

By fire, toxic gases may be formed (COx, NOx).

## Ardex DPM Part B

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

### ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses.

### SPILL CLEAN UP METHODS

Wear necessary protective equipment. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not let washing down water contaminate ponds or waterways.

## 7 HANDLING AND STORAGE

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### STORAGE CLASS

Chemical storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Use chemical cartridge protection with appropriate cartridge.

### HAND PROTECTION

Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

### EYE PROTECTION

Wear tight-fitting goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear, yellowish liquid		
COLOUR	Yellowish		
ODOUR	Amine.		
SOLUBILITY	Immiscible with water		
BOILING POINT (°C)	135	MELTING POINT (°C)	Not determined
RELATIVE DENSITY	1.02	VAPOUR PRESSURE	0.3 kPa
VISCOSITY	600 - 1400 mPas 23	FLASH POINT (°C)	86
AUTO IGNITION TEMPERATURE (°C)	380		

## 10 STABILITY AND REACTIVITY

**Ardex DPM Part B****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Reacts violently with strong oxidising substances.

**HAZARDOUS POLYMERISATION**

Will not polymerise.

**MATERIALS TO AVOID**

Strong oxidising substances. Strong acids.

**HAZARDOUS DECOMPOSITION PRODUCTS**By fire, toxic gases (CO, CO<sub>2</sub>, NO<sub>x</sub>) may be formed.**11 TOXICOLOGICAL INFORMATION****INHALATION**

Harmful by inhalation. May cause sensitisation by inhalation. May cause respiratory allergy.

**INGESTION**

Harmful if swallowed. May cause chemical burns in mouth and throat.

**SKIN CONTACT**

Causes burns. May cause allergic contact eczema. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause sensitisation by skin contact.

**EYE CONTACT**

Causes burns. Extreme irritation of eyes and mucous membranes, including burning and tearing.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LC 50, 96 Hrs, FISH mg/l 10

EC 50, 48 Hrs, DAPHNIA, mg/l 100

IC 50, 72 Hrs, ALGAE, mg/l 79

**WATER HAZARD CLASSIFICATION**

WGK 2

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	8		
PROPER SHIPPING NAME	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S (3-AMINOPROPYLDIMETHYLAMINE, ISOPHORONEDIAMINE)		
UN NO. ROAD	2735	UK ROAD PACK GR.	III
ADR CLASS NO.	8	ADR CLASS	Class 8: Corrosive substances.
ADR PACK GROUP	III	HAZARD No. (ADR)	80
ADR LABEL NO.	8	HAZCHEM CODE	2X
CEFIC TEC(R) NO.	80GC7-II+III	RID CLASS NO.	8
RID PACK GROUP	III	UN NO. SEA	2735
IMDG CLASS	8	IMDG PACK GR.	III
EMS	F-A, S-B	MARINE POLLUTANT	No.

**Ardex DPM Part B**

UN NO. AIR 2735 AIR CLASS 8  
 AIR PACK GR. III

**15 REGULATORY INFORMATION**

## LABELLING



Corrosive

## CONTAINS

3-AMINOPROPYLDIMETHYLAMINE  
 4,4'-ISOPROPYLIDENEDIPHENOL  
 BENZYL ALCOHOL  
 ISOPHORONEDIAMINE  
 m-PHENYLENEBIS(METHYLAMINE)

## RISK PHRASES

R34 Causes burns.  
 R43 May cause sensitisation by skin contact.  
 R20/22 Harmful by inhalation and if swallowed.  
 R62 Possible risk of impaired fertility.

## SAFETY PHRASES

S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
 S51 Use only in well-ventilated areas.  
 S60 This material and its container must be disposed of as hazardous waste.  
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

## APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

REVISION DATE 14/05/2008

REV. NO./REPL. SDS GENERATED 1

## RISK PHRASES IN FULL

R10 Flammable.  
 R20/22 Harmful by inhalation and if swallowed.  
 R21/22 Harmful in contact with skin and if swallowed.  
 R22 Harmful if swallowed.  
 R34 Causes burns.  
 R36/38 Irritating to eyes and skin.  
 R37 Irritating to respiratory system.  
 R41 Risk of serious damage to eyes.  
 R43 May cause sensitisation by skin contact.  
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R62 Possible risk of impaired fertility.

## Ardex DPM Part B

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.